

Options for Sauter Front Linkages



Telescopic top link

- ▶ better adjustment on uneven grounds
 - ▶ lockable
 - ▶ easier coupling and uncoupling
- ## Spindle-adjusted top link



Auxiliary headlights



Front remote outlet

- ▶ connection to „lifting“ conduction
- ▶ for pulled front mowers



Pressure gauge Hydraulic accumulator

- ▶ shock absorber
- ▶ improvement of ride comfort



Angular adapter

- ▶ more clearance for top link of rear linkage



Reversing valve with reducing throttle

- ▶ locking, unlocking
- ▶ single-acting/double-acting
- ▶ continuously adjustable reducing throttle
- ▶ lifting not throttled



Pressure control unit

- ▶ constant weight transfer onto front implement (e.g. packer)
- ▶ adjustment over hand wheel
- ▶ pressure gauge serves for control



2 remote outlets double-acting Big remote outlet Light socket Control from the front



Electronic position control

- ▶ own, high-capacity control unit
- ▶ 2-stage weight adaption
- ▶ continuous control of working position (lifting and lowering)
- ▶ easy handling

SAUTER

Top technology for agriculture



Tractor triangle cat. 2

- ▶ weight of implements upto 1200 kg

Holders for mower relief springs



Ballast container

- ▶ empty weight 220 kg
- ▶ total weight with concrete filling 720 kg, 1000 kg max.
- ▶ with catch hooks size 3L for transport of implements (1000 kg max.)

Ballast support for 3-point seat/for mounting on tractor triangle

- ▶ for fastening of original ballast support
- ▶ total weight upto 1500 kg



Mounting plate for municipal vehicles

- ▶ size 3 or 3/5 (according to DIN 76 060)
- ▶ coupler head
- ▶ opening for cardan shaft

- ▶ short bottom links
- ▶ short top link

- ▶ rigid design (plate can't be moved up and down)
- ▶ slip-on gear, set off
- ▶ quick dismounting



Dealer

All details given and illustrations herein are approximate only and quoted without engagement. Subject to modifications. Design and availability depend on type of tractor and country. The current price-list is always decisive.

SAUTER

Ideas · Machines · Technology

Landman Agricultural Support

Dierenriem 12
 7071 TH Ulfst Nederland
 Telefon ++31 315 640521
 Telefax ++31 315 640531
 E-mail info@landman-agri.com
 Internet www.landman-agri.com

